

APARATI ZA VARENJE

Art.15.440.40 CEN 150/1



Ik max	140A
Prečnik elektroda	2,0-2,5 mm-
Napon praznog hoda	45-48 V
Napon	230V-50Hz
Osigurač	16A
Težina	15,08 kg
Dimenzije pakovanja	400x220x280 mm

Art.15.440.70 NSG 230 F



Napon	230V/400V -50 Hz
Napon praznog hoda	48V
Osigurač	16A
Struja zavarivanja	160A na 230V 200A na 400V
Prečnik elektroda	2,0-4,0 mm



Art.156.440.32 CEN 160/1

Ik mah.	250A
Struja zavarivanja	55-160 A
Elektrode	2-4 mm
Napon praznog hoda	48 V
Osigurač	16A
Težina	22 kg
Dimenzije pakovanja	470x270x340 mm



Art.15.440.90 NSG 270 F

Najbolji rezultati zavarivanja u mobilnoj upotrebi!

Tehnički podaci:

Napon:	230 V/ 400 V ~ 50 Hz
Napon praznog hoda:	48 V
Osigurač:	32 A
Maks. struja zavarivanja:	175 A na 230 V ~ 250 A na 400 V ~
Prečnik elektroda Ø:	2,0 - 5 mm