

# REZAČI PLOČICA



Art.43.011.40 FSG 518/1



Art. 43.012.60 TPR 180 UG



- Motor: ASmotor
- Napon: 230 V ~ 50Hz
- Snaga: 600 W / S2 20min
- Br. obrt. praznog hoda  $n_0$ : 3.000min<sup>-1</sup>
- Visina reza: 90°- 35 mm
- 45°- 12 mm
- Veličina stola: 330 x 360 mm
- Dijamantna rezna ploča: 180 x 25,4 mm
- Težina: 10,8kg
- Dimenzije pakovanja: 380 x 340 x 190 mm

- Asinhroni motor: 230 V ~50 Hz
- Snaga: 600 W
- Broj obrtaja  $n_0$  3,000min<sup>-1</sup>
- Maks. dubina reza: 90°-25mm /45°-17 mm
- Maks.dužina reza kod 15 mm debljine: 360mm
- Maks. dužina reza: 430mm
- Kosi rez: 0° - 45°
- Veličina rezne ploče: Ø 180 x Ø 25.4mm
- Izolacijski razred: IP54



Art.43.012.50 TPR 200/2



Art.43.014.10 TPR 250



- Napon: 230 V ~ 50 Hz
- Snaga: 800 W
- Br. obrt. praznog hoda  $n_0$ : 3000 min<sup>-1</sup>
- Radni sto: 570 x 385 mm
- Radna visina: 700mm
- Maks dubina reza: 90° - 30 mm / 45° - 25mm
- Maks dužina reza: 520 mm
- Kosi rez: 0° - 45°
- Dijamantna ploča: Ø 200 x Ø 25,4mm
- Izolacionirazred: IP54
- Težina: 33,5 kg bruto
- Pakovanje: 89x49x37 cm

- Jednofazni motor: 230 V ~ 50 Hz
- Snaga: 1100W
- Br. obrt. praznog hoda  $n_0$ : 2950 min<sup>-1</sup>
- Dubina reza kod 90°: maks. 65 mm
- Dubina reza kod 45°: maks.48 mm
- Dužina reza do 38 mm: maks. 620 mm
- Dužina reza preko 38mm: maks. 550 mm
- Kosi rez: 0° - 45°
- Dijamantna ploča: Ø 250 x Ø 25,4 mm
- Izolacionirazred: IP54
- Radni sto: 660 x 510mm
- Težina: 56,5 kg bruto
- Pakovanje: 102x59,5x47 cm